MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

MANUFACTURER'S NAME: CAS NUMBER: MIXTURE

MSDS CODE: 012412
ADDRESS:

NFPA HAZARD IDENTIFICATION

DEGREE OF HAZARD HAZARD RATINGS

EMERGENCY TELEPHONE NO.: 0-LEAST

HEALTH: 0 1-SLIGHT
FIRE: 1 2-MODERATE

REACTIVITY: 0 3-HIGH 4-EXTREME

TRADE NAME: LINK BELT HYDRAULIC OILS

SYNONYMS: GRADES - 32, 46

EFFECTIVE DATE: MAY 14, 2002

2. INGREDIENTS

	HAZARDOU	S					
COMPONENT NAME	IN	PERC	PERCENTAGE		COMPONENT		
CAS NUMBER	BLEND	MIN	MAX		EXPOSURE LIMIT		UNIT
BASE LUBRICATING OILS							
MIXTURE	NO	90	TO	95	OSHA PEL	NO	LIMIT
					ACGIH TLV	NO	LIMIT
VISCOSITY INDEX IMPROVER							
MIXTURE	NO	1	TO	5	OSHA PEL	NO	LIMIT
					ACGIH TLV	NO	LIMIT
ANTIWEAR ADDITIVE							
TRADE SECRET	NO	1	TO	5	OSHA PEL	NO	LIMIT
					ACGIH TLV	NO	LIMIT
ANTIFOAM ADDITIVE							
MIXTURE	NO		<	1	OSHA PEL	NO	LIMIT
					ACGIH TLV	NO	LIMIT

3. HEALTH INFORMATION AND PROTECTION

EYE CONTACT: THIS PRODUCT IS PRACTICALLY NON-IRRITATING TO THE EYES UPON DIRECT

CONTACT. BASED ON TESTING OF SIMILAR PRODUCTS AND/OR COMPONENTS.

SKIN CONTACT: AVOID SKIN CONTACT. THIS PRODUCT MAY CAUSE SLIGHT SKIN IRRITATION UPON

DIRECT CONTACT. BASED ON TESTING OF SIMILAR PRODUCTS AND/OR COMPONENTS. PROLONGED OR REPEATED CONTACT MAY RESULT IN CONTACT DERMATITIS WHICH IS CHARACTERIZED BY DRYNESS, CHAPPING, AND REDDENING. THIS CONDITION MAY MAKE THE SKIN MORE SUSCEPTIBLE TO OTHER IRRITANTS, SENSITIZERS, AND DISEASE.

PROLONGED OR REPEATED CONTACT MAY RESULT IN OIL ACNE WHICH IS

CHARACTERIZED BY BLACKHEADS WITH POSSIBLE SECONDARY INFECTION. SEE HEALTH

DATA SECTION BELOW.

INHALATION: THIS PRODUCT HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN

INHALATION HAZARD AT AMBIENT CONDITIONS. CAUTION SHOULD BE TAKEN TO PREVENT AEROSOLIZATION OR MISTING OF THIS PRODUCT. THE PERMISSABLE EXPOSURE LIMIT (PEL) AND THRESHOLD LIMIT VALUE (TLV) FOR THIS PRODUCT AS

OIL MIST IS 5 MG/M3. EXPOSURES BELOW 5 MG/M3 APPEAR TO BE WITHOUT SIGNIFICANT HEALTH RISK. THE SHORT-TERM EXPOSURE LIMIT FOR THIS PRODUCT AS

AN OIL MIST IS 10 MG/M3.

INGESTION: DO NOT INGEST. THIS PRODUCT IS RELATIVELY NON-TOXIC BY INGESTION. THIS

PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND

DIARRHEA. SEE HEALTH DATA SECTION BELOW.

HEALTH DATA: ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO OIL MIST POSES A

RISK OF PULMONARY DISEASE SUCH AS CHRONIC LUNG INFLAMMATION. THIS

CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL

ASPIRATIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER HAS CONCLUDED THAT HIGHLY REFINED MINERAL OILS ARE GROUP 3 SUBSTANCES, "NOT CLASSIFIABLE AS TO THEIR CARCINOGENICITY TO HUMANS," BASED ON INADEQUATE HUMAN AND INADEQUATE

ANIMAL EVIDENCE. THIS SUBSTANCE IS NOT CARCINOGENIC ACCORDING TO THE OSHA

HAZARD COMMUNICATION STANDARD.

4. EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER AND CONTINUE FLUSHING

UNTIL IRRITATION SUBSIDES. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS AND

TAKE VICTIM TO HOSPITAL IMMEDIATELY.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED AREA THOROUGHLY WITH SOAP

AND WATER. IF REDNESS OR IRRITATION OCCURS, SEEK MEDICAL ATTENTION. IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. IF VICTIM IS

SEVERELY BURNED, REMOVE TO A HOSPITAL IMMEDIATELY.

INHALATION: THIS MATERIAL HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN

INHALATION EXPOSURE AT AMBIENT CONDITIONS.

INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

PERSONAL HEALTH PROTECTION INFORMATION 5.

EYE PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF MATERIAL EYE PROTECTION:

IS HANDLED SUCH THAT IT COULD BE SPLASHED INTO EYES, WEAR PLASTIC FACE

PAGE 03

SHIELD OR SPLASH-PROOF SAFETY GOGGLES.

NO SKIN PROTECTION IS REQUIRED FOR SINGLE, SHORT DURATION EXPOSURES. FOR SKIN PROTECTION:

> PROLONGED OR REPEATED EXPOSURES, USE IMPERVIOUS CLOTHING (BOOTS, GLOVES, APRONS, ETC.) OVER PARTS OF THE BODY SUBJECT TO EXPOSURE. IF HANDLING HOT MATERIAL, USE INSULATED PROTECTIVE CLOTHING (BOOTS, GLOVES, APRONS, ETC.). LAUNDER SOILED CLOTHES. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES

INCLUDING SHOES, WHICH CANNOT BE DECONTAMINATED.

RESPIRATORY RESPIRATORY PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF PROTECTION: VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, USE AN

ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER. ALL RESPIRATORS MUST

BE NIOSH CERTIFIED. DO NOT USE COMPRESSED OXYGEN IN HYDROCARBON

ATMOSPHERES.

IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, VENTILATION:

ADEOUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE MUST BE

PROVIDED TO MAINTAIN CONCENTRATIONS BELOW THE SPECIFIED EXPOSURE OR

FLAMMABLE LIMITS.

OTHER: CONSUMPTION OF FOOD AND BEVERAGE SHOULD BE AVOIDED IN WORK AREAS WHERE

HYDROCARBONS ARE PRESENT. ALWAYS WASH HANDS AND FACE WITH SOAP AND WATER

BEFORE EATING, DRINKING, OR SMOKING.

FIRE PROTECTION INFORMATION

FLASH POINT: > 300 F TEST METHOD: C.O.C.

AUTOIGNITION TEMPERATURE: NO DATA TEST METHOD: NO DATA

FLAMMABLE LIMITS IN AIR % BY VOLUME LOWER: NO DATA UPPER: NO DATA

USE DRY CHEMICAL, FOAM, OR CARBON DIOXIDE. EXTINGUISHING

MEDIA:

SPECIAL FIRE WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO FIGHTING HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS

PROCEDURES: FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING

LIQUID.

UNUSUAL FIRE DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION. AND EXPLOSIVE

CONDITIONS:

7. REACTIVITY DATA

STABILITY (THERMAL, LIGHT, ETC.): STABLE

CONDITIONS TO AVOID: NONE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

INCOMPATIBILITY MATERIALS TO AVOID: MAY REACT WITH STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

8. ENVIRONMENTAL PRECAUTIONS

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: CONSULT HEALTH EFFECT INFORMATION IN SECTION III, PERSONAL HEALTH PROTECTION INFORMATION IN SECTION V, FIRE PROTECTION INFORMATION IN SECTION VI, AND REACTIVITY DATA IN SECTION VII. NOTIFY APPROPRIATE AUTHORITIES OF SPILL. CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATERCOURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS, OR OTHER MEANS AND PLACED IN DRUMS OR OTHER SUITABLE CONTAINERS.

WASTE DISPOSAL METHOD:

ALL DISPOSALS MUST COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS. THE MATERIAL, IF SPILLED OR DISCARDED, MAY BE A REGULATED WASTE. REFER TO STATE AND LOCAL REGULATIONS. CAUTION! IF REGULATED SOLVENTS ARE USED TO CLEAN UP SPILLED MATERIAL, THE RESULTING WASTE MIXTURE MAY BE REGULATED. DEPARTMENT OF TRANSPORTATION (DOT) REGULATIONS MAY APPLY FOR TRANSPORTING THIS MATERIAL WHEN SPILLED. WASTE MATERIAL MAY BE LANDFILLED OR INCINERATED AT AN APPROVED FACILITY. MATERIALS SHOULD BE RECYCLED IF POSSIBLE.

9. MISCELLANEOUS

HANDLING AND STORAGE REQUIREMENTS:

DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS. FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106--FLAMMABLE AND COMBUSTIBLE LIQUIDS.

ADDITIONAL INFORMATION:

THIS MIXTURE MAY BE FORMULATED IN PART WITH COMPONENTS PURCHASED FROM OTHER COMPANIES. IN MANY INSTANCES, ESPECIALLY WHEN PROPRIETARY OR TRADE SECRET MATERIALS ARE USED, VISCOSITY OIL COMPANY MUST RELY UPON THE HAZARD EVALUATION OF SUCH COMPONENTS SUBMITTED TO VISCOSITY OIL BY THAT PRODUCT'S MANUFACTURER OR IMPORTER.

THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY SARA TITLE III, SECTION 313 REPORTABLE CHEMICALS AT OR GREATER THAN 1.0% (0.1% FOR CARCINOGENS).

ALL INGREDIENTS OF THIS PRODUCT ARE LISTED ON THE TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY.

DOT: NOT REGULATED BY THE DEPARTMENT OF TRANSPORTATION.

VISCOSITY: < 100 SUS @ 100 F

10. PHYSICAL PROPERTIES

BOILING POINT: > 350 F PERCENT VOLATILE: NIL

MELTING POINT: NOT APPLICABLE VAPOR DENSITY

(AIR=1): NO DATA

APPEARANCE: CLEAR LIGHT LIQUID EVAPORATION RATE

(EE=1): NO DATA

ODOR: PETROLEUM ODOR SPECIFIC GRAVITY: 0.86

VAPOR PRESSURE: NO DATA AVAILABLE MOLECULAR WEIGHT: NO DATA

SOLUBILITY: NEGLIGIBLE IN WATER

DISCLAIMER OF WARRANTY:

THE INFORMATION CONTAINED HEREIN IS BASED UPON DATA AVAILABLE TO US, AND REFLECTS OUR BEST PROFESSIONAL JUDGEMENT. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SUCH DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS OF USE BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.